

WINDOW MOUNTED UNITS (Hybrid Solar AC)

Model No.		SWFR-25GW	SWFR-35GW	SWFR-50GW	SWFR-70GW	
Power Supply: 220-240V 50 / 60HZ 1PH						
Performance						
Capacity	Cooling	Btu/h	9000	12000	18000	24000
		W	2500	3500	5000	7000
	Heating	Btu/h	10000	13000	19000	27000
		W	2700	3800	5500	7500
Noise	Indoor	dB(A)	<35	<39	<42	<46
	Outdoor	dB(A)	≤37	≤40	≤43	≤47
Air Circulation	(med.fan)	m3/h	550	640	900	1150
Suitable Area		m2	15~25	23~33	31~41	40~52
EER		W/W	3.47	3.41	3.32	3.3
		Btu/h/W	11.87	12.01	11.7	12.11
R410 Gas		Grams	600	820	1130	1350
Power Consumption						
Power Input	Cooling	W	600~750	1000~1050	1400~1550	1950~2150
	Heating	W	700	1000	1480	2100
Rated Current	Cooling	A	3.3	4.7	6.8	9.6
	Heating	A	3.1	4.5	6.5	9.4
Dimensions L x H x W (mm)						
Window Panel	Net	535*450*345	600*560*375	670*455*730	670*455*730	
	Shipping	605*570*425	670*610*460	740*575*800	740*575*800	
Plate Collector	Net	1000*550*80	1000*550*80	1000*555*80	1000*555*80	
	Shipping	1145*620*110	1145*620*110	1145*620*110	1145*620*110	
Vaccuum Tube	Net	910*400*330	910*400*330	970*400*370	970*400*370	
	Shipping	600*500*425	670*610*460	740*525*800	740*525*800	
	Dia*L* No.	47 dia*520*10off	47 dia*520*10off	47dia*640*11off	47dia*640*11off	
Weight N.W./G.W.						
Window Panel	Net/Gross	kg	33/35	42/45	59/61	69/73
Solar Collector	Net/Gross	kg	14/16	14/16	14/16	14/16

